

Series PSD Suction Diffusers

Available in sizes 2" - 12"

For general purpose applications
in chilled, condenser, heating
and cooling tower systems.

A single PACO Suction Diffuser
eliminates the need for separate:

- 90° Elbow
- Strainer
- Flow Stabilizer
- Reducer (when required)

Designed to:

- Reduce Material Cost
- Reduce Installation Cost
- Reduce Space Requirements
- Reduce Maintenance Cost
- Extend Life of Pump

Maximum Working Pressure:
175 PSIG

Maximum Working Temperature:
300°F



FEATURES AND BENEFITS

Combined Functions – One fitting replaces a 90° ell, strainer, flow stabilizer and reducer, simplifying installation and reducing installation cost.


Space Savings – Use a PACO PSD suction diffuser whenever floor space does not permit recommended 10 pipe diameters of straight suction piping. Diffuser incorporates flow-straightening guide vanes to promote smooth, even flow profile as fluid enters pump suction thereby maximizing pump life.

Strainer – Diffuser incorporates a permanent, perforated stainless steel strainer and a disposable stainless steel, fine-mesh start-up screen for capture and removal of foreign particulates in system piping. Clean fluid, free of suspended solids helps protect pump and other system components.

Ease of Installation -- Cast iron body and cover with 125# ANSI flanges are suitable for direct mounting to suction of pump.

PACO Suction Diffusers Series PSD


Key No	Description	Material
1	Body	Cast Iron
2	Strainer	304SS
3	Mesh Grid	304SS
4	Cover	Cast Iron
5	Cap Screw	Steel
6	O Ring	Buna N
7	Plug	Malleable Iron



PRESSURE LOSS

(Caution: Verify Pump NPSH requirements)

Model	Curve
PSD2015-125	A
PSD2020-125	B
PSD2520-125	B
PSD2525-125	C
PSD3020-125	B
PSD3025-125	C
PSD3030-125	D
PSD4030-125	D
PSD4040-125	E
PSD5040-125	E
PSD5050-125	F
PSD6040-125	E
PSD6050-125	F
PSD6060-125	G
PSD8060-125	G
PSD8080-125	H
PSD1080-125	H
PSD1010-125	I
PSD1280-125	H
PSD1210-125	I
PSD1212-125	J



Typical Specifications

Furnish and install directly on the suction inlet of each pumping unit a PACO Series PSD Suction Diffuser with flanged cast iron body and flow straightening vanes. Diffuser shall be equipped with a permanent strainer constructed of perforated stainless steel and a stainless steel, disposable start-up screen which shall be removed and disposed of after one month operation. Diffuser size shall be compatible with pump suction inlet size and pipe size.



800 Koomey Road
Brookshire, TX 77423
1-800-926-6688
www.paco-pumps.com